


### Product details

CONNECTIVITY MODE	Brain server client, WebSocket/http client, tcp server
DATA EXCHANGE	JSON
DEVICE WEB PORTAL	Yes (IP settings)
SERVICES	Presences, Hits, Sense&Control, Spotsets
CONNECTIVITY INTERFACES	RJ45 Ethernet (100Mbit)
OPTICALLY ISOLATED GPIO	Externally powered (5-24VDC), 2x inputs & 2x outputs (switched, max 300mA)
TEMPERATURE	Operation -25C to +60C, Storage -40C to +75C
POWER CONSUMPTION	12W peak, 11W continues.
POWER SOURCES	PoE (IEEE 802.3af), 12-15VDC
COMPLIANCE	ETSI EN 302208-1 EN 302208-2
IP-CLASS	IP30

### Generic specification



### UHF RFID

PROTOCOL	EPCglobal UHF Class1 GEN2, ISO/IEC 18000-63
READ RANGE	Up to > 10m (depending on tag and antenna) up to 100m <sup>2</sup> (radius 5.5m, mounting height 4.5m)
OUTPUT POWER	Antenna ports 5-30dBm, built-in antennas 11-36dBm ERP
FREQUENCY RANGE	ETSI - 865.6-867.6MHz, FCC - 902-928MHz
ANTENNA PORTS	2x SMA Female (50 Ohm)
BUILT-IN ANTENNAS	6x Linear-polarized (3x horizontal, 3x vertical)
CHIPSET	Impinj R2000
COMPLIANCE	ETSI EN 302208 v3.1.1, ETSI EN 302208-1, ETSI EN 302208-2, FCC Rule Parts 15c


### BLUETOOTH LOW ENERGY (BLE)

SUPPORTED PROTOCOLS	iBeacon, Intellifi Bluetitan, Eddystone (UID)
RANGE	Up to 150m LoS, up to 50m indoor (depending on tag and setup)
OUTPUT POWER	Up to +8dBm EIRP
FREQUENCY	2,4 GHz
ANTENNA PORTS	None
BUILT-IN ANTENNAS	2x BLE (transceiver, receiver)
CONCURRENT CONNECTIONS	8x Relay BLE
CONCURRENT CHANNEL MONITORING	3x Parallel on 37, 38, 39
COMPLIANCE	EN 000328

### DIMENSIONS AND WEIGHT

DIMENSIONS (WxHxD)	595mm x 595mm x 77mm / 23.4" x 23.4" x 3"
WEIGHT	4.7kg / 10.4lbs
MOUNTING	VESA 100 M4 threaded (100x100mm / 3.94" x 3.49")
INCLUDED IN PACKAGE	100-240VAC to 12VDC universal power adapter, reset tool, pluggable 8-pin terminal block, 4x M4x12mm

### ANTENNA RADIATION PATTERN



### COMPATIBLE PRODUCTS

INTELLIFI COMPATIBLE PRODUCTS	Antenna RFID, Relay BLE, Bluetitan
-------------------------------	------------------------------------

